
BookletChart

Key West Harbor and Approaches

(NOAA Chart 11441)





A reduced scale NOAA nautical chart for small boaters. When possible, use the full size NOAA chart for navigation.

- ☑ Complete, reduced scale nautical chart
- ✓ Print at home for free
- ☑ Up to date with all Notices to Mariners

Home Edition (not for sale)

- ☑ United States Coast Pilot excerpts
- ✓ Compiled by NOAA, the nation's C AND ATMOSPHER chartmaker.





What are Nautical Charts?

Nautical charts are a fundamental tool of marine navigation. They show water depths, obstructions, buoys, other aids to navigation, and much more. The information is shown in a way that promotes safe and efficient navigation. Chart carriage is mandatory on the commercial ships that carry America's commerce. They are also used on every Navy and Coast Guard ship, fishing and passenger vessels, and are widely carried by recreational boaters.

What is a BookletChart[™]?


This BookletChart is made to help recreational boaters locate themselves on the water. It has been reduced in scale for convenience, but otherwise contains all the information of the full-scale nautical chart. The bar scales have also been reduced, and are accurate when used to measure distances in this BookletChart. See the Note at the bottom of page 5 for the reduction in scale applied to this chart.

Whenever possible, use the official, full scale NOAA nautical chart for navigation. Nautical chart sales agents are listed on the Internet at http://www.NauticalCharts.NOAA.gov.

This BookletChart does NOT fulfill chart carriage requirements for regulated commercial vessels under Titles 33 and 44 of the Code of Federal Regulations.

Notice to Mariners Correction Status

This BookletChart has been updated for chart corrections published in the U.S. Coast Guard Local Notice to Mariners, the National Geospatial Intelligence Agency Weekly Notice to Mariners, and, where applicable, the Canadian Coast Guard Notice to Mariners. Additional chart corrections have been made by NOAA in advance of their publication in a Notice to Mariners. The last Notices to Mariners applied to this chart are listed in the Note at the bottom of page 7. Coast Pilot excerpts are not being corrected.



[Coast Pilot 5, Chapter 4 excerpts]

- (18) **Key West Harbor** is in front of the city of Key West. The harbor is entered through breaks in the reef by several principal channels with depths of about 13 to 33 feet, and several minor channels.
- (22) Main Ship Channel is the deep-draft approach. Federal project depth is 34 feet from the Straits of Florida to a turning basin off the Naval Air Station Truman Annex Mole and inside the annex basin, thence 30 feet to an upper turning basin off Key West

Bight, and then 12 feet to and including a turning basin in the bight. (23) **Northwest Channel** is a passage between Key West Harbor and the Gulf of Mexico. The depth was 12 feet. Vessels can pass directly across the reefs from the Gulf to the Straits of Florida by way of Northwest Channel and Main Ship Channel.

- (24) The jetties on either side of the Gulf entrance to Northwest Channel are 0.3 to 0.5 mile from the centerline of the channel, and only the outer part of the E jetty shows above low water. The NW end of the jetty is marked by a light. The channel is marked by lights, a **166**° lighted range, daybeacons, and lighted and unlighted buoys.
- (26) **Southwest Channel** has been swept to a depth of 23 feet and is marked by buoys. Strangers should not attempt passage at night.
- (27) **West Channel** is deep but unmarked. It is used by shrimp boats and small craft bound toward the Dry Tortugas. Local knowledge is advised for safe passage.
- (28) **Calda Channel** is narrow and crooked, but well marked by daybeacons and a light at the N end. The depth was 3 feet except for shoaling close to the aids marking the channel. The channel should be used only with local knowledge and during good visibility.
- (29) **Garrison Bight Channel;** the depth was 6.5 feet with 8.0 feet in the turning basin. A channel leads from the turning basin to a basin in the SW part of the bight. The channel had a depth of 5 feet.
- (31) Garrison Bight has excellent small-craft facilities.
- (32) The best anchorage for medium-draft vessels less than 200 feet long is in **Man of War Harbor** where depths are 14 to 26 feet. Mariners should exercise caution to avoid the visible and submerged wrecks in the harbor. It is protected against heavy seas. Small craft usually anchor E of **Wisteria Island**. Anchoring in the vicinity of Key West Bight Channel Light 2, between Key West Bight Channel and the shoreline, is not recommended because of poor holding ground, strong currents, and obstruction of the dock approaches.
- (33) Vessels can anchor W of the city in depths of 20 to 26 feet, taking care to avoid the reefs which rise abruptly in some places along the edges of the channels.
- (35) **Naval restricted areas** are off the S, W, and N sides of Key West. A **restricted area** extends about 150 yards from the shoreline around Fleming Key.
- (36) A **naval operational training area**, aerial gunnery range, and bombing and strafing target **danger zones** are in the Straits of Florida and the Gulf of Mexico in the vicinity of Key West.
- (41) **Currents.** A W current, counter to the prevailing E set of the Gulf Stream, at times exceeding 1 knot, has been reported in the vicinity of Key West Entrance Lighted Whistle Buoy. In the main channel W of Fort Taylor, the flood (NNE) and the ebb (SSW) currents at strength average 1.0 knot and 1.7 knots, respectively. In the upper turning basin, the flood sets NE and the ebb SW with averages at strength of 0.8 and 1.1 knots, respectively. In Northwest Channel about 2.5 and 5.5 miles from Key West, the tidal currents average 1.3 knots and 0.6 knot, respectively. It was reported that the current in the channel between Fleming Key and Key West reaches 6 knots during both flood and ebb, with currents of up to 9 knots having been observed N of Pier D-3 at the W end of the channel.
- (67) **Key West Coast Guard Station** is at Pier D-2 on the NW side of Key West.
- (68) A 5-mph **speed limit** is enforced in Garrison Bight and in all constricted channel areas.
- (82) Small-craft facilities. Berths, electricity, water, ice, and some marine supplies are available at Key West. Gasoline and diesel fuel are available at Key West Bight and Garrison Bight. Small craft moor in Key West Bight, and in Garrison Bight at the Municipal Marina, or at the Key West Yacht Club, which are at the SW and E ends of the bight,. Anchoring or mooring elsewhere in Garrison Bight, except in an emergency or as a shelter during bad weather, is not permitted. Public launching ramps are in Garrison Bight and at the foot of Simonton Street. (84) Boca Chica Key. A naval restricted area extends about 150 yards from the shoreline along a portion of the NE side of the Naval Air Station. Boca Chica Channel with a depth of 9 feet is marked by a light at the entrance, thence by lights and daybeacons. The basin provides a good hurricane anchorage for small vessels in emergencies only..



Corrected through NM Sep. 23/06 Corrected through LNM Sep. 19/06

HEIGHTS

Heights in feet above Mean High Water

For Symbols and Abbreviations see Chart No. 1

CAUTION

SUBMARINE PIPELINES AND CABLES

Charted submarine pipelines and submarine ables and submarine pipeline and cable areas

Additional uncharted submarine pipelines and submarine cables may exist within the area of this chart. Not all submarine pipelines and sub-marine cables are required to be buried, and those that were originally buried may have secome exposed. Mariners should use extreme aution when operating vessels in depths of water comparable to their draft in areas where opelines and cables may exist, and when anchoring, dragging, or trawling.

Covered wells may be marked by lighted or unlighted buoys.

PROHIBITED AREAS (Areas to be avoided)

SUPPLEMENTAL INFORMATION

Consult U.S. Coast Pilots 4 and 5 for important supplemental information.

PARTICULARLY SENSITIVE SEA AREA

PARTICULARITY SENSITIVE SEA AREA
This chart falls entirely within the limits of a
Particularly Sensitive Sea Area (PSSA), A
PSSA is an environmentally sensitive area
around which mariners should exercise
extreme caution. See U.S. Coast Pilot volumes
for information regarding this area.

HORIZONTAL DATUM

The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which North American Datum of 1983 (NAID 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84), Geographic positions referred to the North American Datum of 1927 must be corrected an average of 1.528* northward and 0.668* eastward to agree with this chart.

RADAR REFLECTORS

Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

NOAA WEATHER RADIO BROADCASTS

NOAA WEATHER HADIO BROADCASTS

The NOAA Weather Radio station listed below provides continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be as much as 100 nautical miles for stations at high elevations.

CALITION

Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

AIDS TO NAVIGATION

וס מום IO NAVIGATION

Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

CAUTION

Limitations on the use of radio signals as Limitations on the use of radio signals as aids to marrien navigation can be found in the U.S. Coast Guard Light Lists and National Imagery and Mapping Agency Publication 117. Radio direction-finder bearings to commercial broadcasting stations are subject to error and should be used with caution.

Station positions are shown thus:

(Accurate location) o(Approximate location)

Table of Selected Chart Notes

12 HURRICANES AND TROPICAL STORMS

Hurricanes, tropical storms and other major storms may cause considerable damage to marine structures, aids to navigation and moored vessels, resulting in submerged debris in unknown locations.

in unknown locations.

In unknown locations, channel depths and shoreline may not reflect actual conditions following these storms. Fixed aids to navigation may have been damaged or destroyed. Buoys may have been moved from their charled positions, damaged, sunk, extinguished or otherwise made inoperative. Mariners should not rely upon the position or operation of an aid to navigation. Wirecks and submerged obstructions may have been displaced from charted locations. Pipelines may have become uncovered or moved.

or moved.

Mariners are urged to exercise extreme caution and are requested to report aids to navigation discrepancies and hazards to navigation to the nearest United States Coast Guard

NOTE A

Navigation regulations are published in Chapter 2, U.S.

Coast Pliots 4 and 5. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 7th Coast Guard District in Miami, Florida, or at the Office of the District Engineer, Corps of Engineers in Jacksonville

Refer to charted regulation section numbers

WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

Additional information can be obtained at nauticalcharts.noaa.gov

AUTHORITIES

Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the Corps of Engineers, U.S. Coast Guard, and National Geospatial-Intelligence Agency.

POLLUTION REPORTS

REPORTS
Report all spills of oil and hazardous substances to the National
Response Center via 1-800-424-8802 (toll free), or to the nearest U.S.
Coast Guard facility if telephone communication is impossible (33 CFR 153).

SOURCE DIAGRAM

The outlined areas represent the limits of the most recent hydrographic survey information that has been evaluated for charting. Surveys have been banded in this diagram by date and type of survey. Channels maintained by the U.S. Army Corps of Engineers are periodically resurveyed and are not shown on this diagram. Refer to Chapter 1, <u>United States Coast Pilot</u>.

NOTE S

Regulations for Ocean Dumping Sites are contained in 40 CFR, Parts 220-229. Additional information concerning the regulations and requirements for use of the sites may be obtained from the Environmental Protection Agency (EPA). See U.S. Coast Plots appendix for addresses of EPA offices. Dumping subsequent to the survey dates may have reduced the depths shown.

Within the 12-nautical mile Territorial Sea, established by Presidential Proclamation, some Federal laws apply. The Three Nautical Mile Line, previously identified as the outer limit of the territorial sea, is retained as it continues to depict the jurisdictional limit of the other laws. The P-nautical mile Natural Resource Boundary of the Gulf coast of Florida, Texas, and Puerto Rico, and the Three Nautical Mile Line elsewhere remain in most cases the inner limit of Federal fisheries jurisdiction and the outer limit of the jurisdiction of the states. The 24-nautical mile Contiguous Zone and the 200-nautical mile Exclusive Economic Zone were established by Presidential Proclamation. Unless fixed by treaty or the U.S. Supreme Court, these maritime limits are subject to modification.

This nautical chart has been designed to promote safe navigation. The National Ocean Service encourages users to submit corrections, additions, or comments for improving this chart to the Chief, Marine Chart Division (N/CS2), National Ocean Service, NOAA, Silver Spring, Maryland 20910-3282.

COLREGS, 80.740 (see note A)


International Regulations for Preventing Collisions at Sea, 1972.


The entire area of this chart falls seaward of the COLREGS Demarcation Line.


TIDAL INFORMATION

PLACE		Height referred to datum of soundings (MLLW)		
NAME	(LAT/LONG)	Mean Higher High Water	Mean High Water	Mean Low Water
		feet	feet	feet
Sand Key Lighthouse	(24°27'N/081°53'W)	1.7	1.4	0.2
Key West	(24°33'N/081°49'W)	1.8	1.5	0.2
Dashes () located in datum columns indicate unavailable datum values for a tide station. Real-time water levels,				

tide predictions, and tidal current predictions are available on the Internet from http://tidesandcurrents.noaa.gov












Joins page 1


























promote safe navigation. The National orrections, additions, or comments for lart Division (N/CS2) National Ocean i10-3282.


PUDISINGE AT WASHINGTON, D.G.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINIS
NATIONAL OCEAN SERVICE
COAST SURVEY



Published at Washington, D.C.
DEPARTMENT OF COMMERCE
ANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE







EMERGENCY INFORMATION

VHF Marine Radio channels for use on the waterways:

Channel 6 – Inter-ship safety communications.

Channel 9 – Communications between boats and ship-to-coast.

Channel 13 – Navigation purposes at bridges, locks, and harbors.

Channel 16 – Emergency, distress and safety calls

to Coast Guard and others, and to initiate calls to other vessels. Contact the other vessel, agree to another channel, and then switch.

Channel 22A – Calls between the Coast Guard and the public. Severe weather warnings, hazards to navigation and safety warnings are broadcast here.

Channels 68, 69, 71, 72 & 78A – Recreational boat channels.

Distress Call Procedures

- 1. Make sure radio is on.
- 2. Select Channel 16.
- 3. Press/Hold the transmit button.
- 4. Clearly say: "MAYDAY, MAYDAY, MAYDAY."
- Also give: Vessel Name and/or Description; Position and/or Location; Nature of Emergency; Number of People on Board.
- 6. Release transmit button.
- Wait for 10 seconds If no response Repeat MAYDAY Call.

HAVE ALL PERSONS PUT ON LIFE JACKETS!!

Mobile Phones – Call 911 for water rescue.

Coast Guard Group Key West – 305-292-8856 Coast Guard Key West – 305-295-9700 FL Fish and Wildlife Conservation Comm – 888-404-3922

Coast Guard Atlantic Area Cmd - 757-398-6390

<u>NOAA Weather Radio</u> – 162.400 MHz, 162.425 MHz, 162.450 MHz, 162.475 MHz, 162.500 MHz, 162.525 MHz, 162.550 MHz.

<u>Getting and Giving Help</u> – Signal other boaters using visual distress signals (flares, orange flag, lights, arm signals); whistles; horns; and on your VHF radio. You are required by law to help boaters in trouble. Respond to distress signals, but do not endanger yourself.



NOAA CHARTING PUBLICATIONS

Official NOAA Nautical Charts – NOAA surveys and charts the national and territorial waters of the U.S, including the Great Lakes. We produce over 1,000 traditional nautical charts covering 3.4 million square nautical miles. Carriage of official NOAA charts is mandatory on the commercial ships that carry our commerce. They are used on every Navy and Coast Guard ship, fishing and passenger vessels, and are widely carried by recreational boaters. NOAA charts are available from official chart agents listed at: www.NauticalCharts.NOAA.gov.

Official Print-on-Demand Nautical Charts – These full-scale NOAA charts are updated weekly by NOAA for all Notice to Mariner corrections. They have additional information added in the margin to supplement the chart. Print-on-Demand charts meet all federal chart carriage regulations for charts and updating. Produced under a public/private partnership between NOAA and OceanGrafix, LLC, suppliers of these premium charts are listed at www.oceanGrafix.com.

Official Electronic Navigational Charts (NOAA ENCs®) –

ENCs are digital files of each chart's features and their attributes for use in computer-based navigation systems. ENCs comply with standards of the International Hydrographic Organization. ENCs and their updates are available for free from NOAA at www.NauticalCharts.NOAA.gov.

Official Raster Navigational Charts (NOAA RNCs[™]) –

RNCs are geo-referenced digital pictures of NOAA's charts that are suitable for use in computer-based navigation systems. RNCs comply with standards of the International Hydrographic Organization. RNCs and their updates are available for free from NOAA at www.NauticalCharts.NOAA.gov.

Official BookletCharts[™] – BookletCharts[™] are reduced scale NOAA charts organized in page-sized pieces. The "Home Edition" can be downloaded from NOAA for free and printed. The Internet address is www.NauticalCharts.gov/bookletcharts.

Official PocketChartsTM – PocketChartsTM are for beginning recreational boaters to use for planning and locating, but not for real navigation. Measuring a convenient 13" by 19", they have a 1/3 scale chart on one side, and safety, boating, and educational information on the reverse. They can be purchased at retail outlets and on the Internet.

Official U.S. Coast Pilot® – The Coast Pilots are 9 text volumes containing information important to navigators such as channel descriptions, port facilities, anchorages, bridge and cable clearances, currents, prominent features, weather, dangers, and Federal Regulations. They supplement the charts and are available from NOAA chart agents or may be downloaded for free at www.NauticalCharts.NOAA.gov.

Official On-Line Chart Viewer – All NOAA nautical charts are viewable here on-line using any Internet browser. Each chart is up-to-date with the most recent Notices to Mariners. Use these on-line charts as a ready reference or planning tool. The Internet address is www.NauticalCharts.gov/viewer.

Official Nautical Chart Catalogs – Large format, regional catalogs are available for free from official chart agents. Page size, state catalogs are posted on the Internet and can be printed at home for free. Go to http://NauticalCharts.NOAA.gov/mcd/ccatalogs.htm.

Internet Sites: www.Noa.gov, <a href="